

SOLIS

THE TOUGHEST
PERFORMER
FOR YOUR FIELD

26



RELIABLE MECHANICAL
TRACTOR

POWER PACKED
ENGINE

TWIN PROJECTOR
HEADLAMPS

AGRI, IND. & TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

THE TOUGHEST PERFORMER FOR YOUR FIELD

S26


Solis



FEATURES	S26
ENGINE	
Engine Type	MHI Engine
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	2700
Air Cleaner	Dry Type with Clogging Sensor
Cold Start	Standard
Max Torque (Nm)	76.3 Nm
Exhaust	Downdraft Exhaust
Muffler	Under-hood
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD) Agri Tyre	
Maximum Speed (Km/Hr)	18.08
Minimum Speed (Km/Hr)	1.67 @ 2700 rpm Speeds May Vary with Other Tyres
BRAKES	
Brakes	Oil Immersed Brakes
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Mechanical, Foot Operated
PTO	
PTO (RPM)	540/1000
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 65Ah
Alternator	12V, 42Amp
Seven Pin Trailer Socket	Output 12V
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Hydraulic Lifting Capacity (Kg)	600
Auxiliary Hydraulic Circuit	1DA
SAFETY SWITCH	
Clutch Safety Switch	Standard

FEATURES	S26			
PTO Safety Switch	Standard			
Neutral Safety Switch	Standard			
CAPACITY (Ltrs.) (+/-5%)				
Fuel Tank (Ltr.)	26			
TURNING RADIUS				
With Brakes (m)	2.7			
TYRE				
Front	6.00 - 12			
Rear	8.30 - 20			
DIMENSION & WEIGHT (+/-5%) Agri Tyre				
Weight (Kg)	995			
Wheel Base (mm)	1560			
Total Length (mm)	2760			
Total Width (mm)	1075			
Height (mm) Up to ROPS	1955			
Min. Ground Clearance (mm)	240			
Front Track (mm)	885			
Rear Track (mm)	835			
OTHERS				
Fuel Indicator Gauge	Standard			
Front Tow Hook	Standard			
Front & Rear Weights with Std. Ballast	Front Weights - 15 x 2			
Trailer Hitch	1. Swinging Bar (Optional) 2. Clevis Hitch (Standard) 3. Semi Automatic Hitch			
Roll Over Protection	Standard			
Canopy	Optional			
OPTIONAL FEATURES				
TYRES				
TURF Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5	INDUSTRIAL Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5	AGRI Front Tyre: 7x14 Rear Tyre: 8.3x24	RADIAL Front Tyre: 6.5/80-12 Rear Tyre: 280/70 R18	GALAXY PRO Front Tyre: 220/55 R12 Rear Tyre: 280/70 R16
Front End Loader	Optional			

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com