

Solis

FUTURE IS NOW

7520N



4 CYLINDER
TURBOCHARGED ENGINE



ADVANCE EUROPEAN
AERODYNAMIC STYLING




FACTORY FITTED
FRONT WEIGHTS



STYLISH TWIN
PROJECTOR LAMPS



LOW TURNING RADIUS



SYNCHRO SHUTTLE
TRANSMISSION WITH CREEPER



POWER STEERING












HYDRAULIC LIFTING
CAPACITY 2500 KG










SHUTTLEXL

SUPER
YNCHRO >> GEAR SHIFT ON THE GO >>>

www.solistractors.com

FEATURES	Solis 7520N
ENGINE 	
Engine Type	4 Cylinder, Turbocharged Engine
HP Category	75 HP
No. of Cylinders	4
Aspiration	Turbocharged
Cubic Capacity (cc)	3707
Rated RPM	2000
Air Cleaner	Dry Air Cleaner with Clogging Sensor
Cold Start	Yes
Max Torque (Nm) ± 5%	289Nm @ 1300
Exhaust	Underhood Downdraft Towards the Floor
TRANSMISSION 	
Clutch	Double Clutch
Gearbox	12F+12R
Front Axle	4WD
Transmission	Carraro Synchromesh Shuttle Transmission with Creeper
SPEED (FORWARD) 	
Maximum Speed (Km/Hr)	28.27 kmph (with Agri Tyre)
Minimum Speed (Km/Hr)	0.46 kmph (with Agri Tyre)
BRAKES 	
Brakes	Oil Immeresed Brake
Type of Actuation	Mechanical
Parking Brake	Independent Type
DIFFERENTIAL LOCK 	
Differential Lock	Yes, Foot Operated
PTO 	
PTO (RPM)	540/540E
PTO (Actuation)	Mechanical
STEERING 	
Steering	Power
ELECTRICAL 	
Battery	12V, 85Ah
Alternator	12V, 90Amp
Seven Pin Trailer Socket	Yes
HYDRAULICS 	
3 Point Linkage	CAT-II

FEATURES	Solis 7520N
Stay Bars	Standard
Hydraulic Lifting Capacity (Kg)	2500
Auxiliary Hydraulic Circuit	2DA/2SA/3DA (Optional)
SAFETY SWITCH 	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
CAPACITY (LTRS)(+/-5%) 	
Fuel Tank (Ltr.)	73
TURNING RADIUS 	
Without Brakes (m)	4.26
TYRE 	
Front	8-18
Rear	14.9-24
DIMENSION (+/-5%) (4WD/2WD) 	
Weight (Kg)	2735
Overall Length (mm)	4020-4245
Overall Width (mm)	1475-1606
Overall Height (mm)	2630
Wheel Base (mm)	2310
Min. Ground Clearance (mm)	256
Front Wheel Track Agri (mm)	1150-1286
Rear Wheel Track Agri (mm)	1082-1213
OTHERS 	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard, Inbuilt in Front Weight
Front & Rear Weights with Std. Ballast	Front-72 Kg + 6x31 Kg Front Removal Weight. / Rear 1*30 Kg At Each Wheel
Trailer Hitch	Swinging Drawbar
Front Mudguard	Standard
OPTIONAL FEATURES 	
Tyres	4WD 1) Front Tyre: 260/70R16 Rear Tyre: 360/70R24 2) Front Tyre: 280/70R18 Rear Tyre: 360/70R28 3) Front Tyre: 280/70R18 Rear Tyre: 420/70R24 2WD 4) Front Tyre: 6.5x16 Rear Tyre: 360/70/R28 5) Front Tyre: 6.0x16 Rear Tyre: 360/70/R24 6) Front Tyre: 6.5x16 Rear Tyre: 420/70R24
Cabin	HVAC

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

The Solis 7520N is a meticulously designed narrow tractor with power steering, perfect for precise tasks like mulching, mowing, and crop protection. Its robust frame combines durability and versatility, making it an ideal choice for vineyard and orchard farming. With ample space, efficient transmission, advanced hydraulics, and comfortable ergonomics, the Solis 7520N excels in performance and maneuverability, enhancing productivity in various agricultural operations.



Dealership stamp

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com